

## Supply and Delivery of Sound/Audio System

Item No.	QTY	Unit	Item Description	Unit Cost	Total Cost
1	1	lot	<b>Audio System</b>	267,000.00	267,000.00
<b>BREAKDOWN:</b>					
1.1	4 pcs		High-powered active speakers , 2000 watts RMS, 15" 1x15 high power transducer 50mm voice coil, built-in bi-amp power amplifier module, master/bass/treble control, switchable between mic and line input		
1.2	1 set		Digital mixer - 18 channels, 12 bus digital mixer w/ ipad/tablet controller 18 input digital mixer for studio and live application, 18x18 channel, bi directional USB interface for direct recording, with tablet or iphone controller		
1.3	1 roll		Signal cable (mic cable 2+1) heavy duty, with 10 male XLR connector and 10 XLR female connector, heavy duty		
2	1 lot		<b>Audio System (for satellite campuses)</b>	150,000.00	300,000.00
<b>BREAKDOWN</b>					
2.1	Two (2 ) Sets	Sound System	Powered Speakers: High-Power 1,000-Watt 2-way 12" PA sound reinforcement speaker system, Ultra-compact and lightweight system, High-performance Bluetooth* A2DP technology, 2-channel mixer with individual Mic/Line inputs, Volume controls and Clip LEDs, Dedicated 2-band EQ plus integrated sound processor, Extremely powerful 12" long-excursion driver, 1" compression driver, Ultra-wide dispersion, large-format exponential horn, Additional Line output, Versatile trapezoidal enclosure design allows different positioning: - Stand mounting with 35 mm pole socket - Tilts on its side for use as a floor monitor, with speaker stand: heavy duty, aluminum, match with powered speakers, 38 inches		
2.2	Two (2 ) pcs	Audio Mixer:	16-Channel Mixing Console: Max. 10 Mic / 16 Line Inputs (8 mono + 4 stereo) / 4 GROUP Buses + 1 Stereo Bus / 4 AUX (incl. FX) MG16XU, 16-Channel Mixing Console, Max. 10 Mic / 16 Line Inputs (8 mono + 4 stereo), 4 GROUP Buses + 1 Stereo Bus, 4 AUX (incl. FX), "D-PRE" mic preamps with an inverted Darlington circuit, 1-Knob compressors, High-grade effects: SPX with 24 programs, 24-bit / 192kHz 2in / 2out USB Audio functions, Works with the iPad (2 or later) through the Apple iPad Camera Connection Kit / Lightning to USB Camera Adapter, Includes Cubase AI DAW software download version, Cubasis LE for iPad available at App Store, PAD switch on mono inputs, +48V phantom power, Internal Universal Power Supply for world-wide use, XLR balanced outputs, Optional Rack Mount Kit RK-MG12, Metal chassis, Dimensions(W×H×D): 444 mm x 130 mm x 500 mm (17.5" x 5.1" x 19.7")		
2.3	Two (2 ) pcs	Wireless microphone:	CPU-controlled diversity. "NoiseLock" squelch, , receiver panel with easy-to-read displays and user-friendly functions, receiver equipped with a balanced volume control, system's default output level is accurately pre-adjusted, equipped with a "receiving sensitivity adjustor" on the receiver front panel, equipped with a "NOISE" LED indicator, UHF 760~950MHz, 60Hz~18KHz, equipped high-pass filter circuitry, maximum output level: Three options: +10dBV / 0dBV / -6dBV, Light, rugged housing, powered by dual AA batteries.		
2.4	Two (2 ) set	Cables	: 10 pcs XLR connectors male, 10 pcs XLR connectors female, all heavy duty, for audio setup 2 pcs HDMI Cables at 10 meters each		
			xxxx	<b>TOTAL</b>	<b>567,000.00</b>
<p style="text-align: center;"><b>The brand has been in the market in the past 20 years with good standing, with the service center in the Philippines, warranty in parts and services of 1-year minimum, Genuine Product.</b></p>					