

Republic of the Philippines

## BENGUET STATE UNIVERSITY

La Trinidad, Benguet

## **PURCHASE ORDER**

| Supplier:   |          | LEVINS INTERNATIONAL CORPORATION            |   | P.O No.:  | ○ No.: 2023-08-IGI- 225    |            |   |  |
|---|----------|---|---|---|----------------------------|------------|---|--|
| Address:  |          | Quezon Ci                                   | ty  | Date:   | AUG 0 9 2023               |            |   |  |
| Tin:  |          |   |   | Mode of<br>Procurement:                               | Public Bidding- IB 2023-18 |            |   |  |
|   |          |   |   | PR No.:   | 2023-518                   |            |   |  |
| Gentlemen:  |          |   |   |   |                            |            |   |  |
| Please furnish this Office the following articles subject to the terms and conditions contained herein: |          |   |   |   |                            |            |   |  |
| Place of De   | elivery: | BSU -SP                                     | PMO   | Delivery  | FOB DESTINATION            |            |   |  |
| Date of Delivery:   |          | WITHIN 45 CALENDAR DAYS UPON RECEIPT OF P.O |   | Term:<br>Payment                                      |                            |            | e delivery  |  |
| Item no. Stock/Pro perty No.  |          | Unit ITEM                                   |   | Term:<br>Quantity                                     | Unit Cost                  | Amount     | End User  |  |
| 4   |          | unit  | VERTICAL LAMINAR FLOW - Vertical Laminar Flow - Model BBS-V800 Biobase. Dimensions: Internal Size (WDH) 800*530*540mm. Work Surface Height: 660mm. Display: LED. Airflow Velocity: Average of 0.3-0.5m/s, air speed adjustable. Material: Main Body: Cold-rolled steel with anti-bacteria power coating. work Table: 304 stainless steel. Pre-Filter: Polyester fiber, washable. HEPA Filter: 99.999% efficiency at 0.3 µm. Noise: <65dB. Front window: Manual; 5mm toughened glass, anti UV. Max opening 490mm. Illuminating Lamp: LED Lamp; 8W*1; UV Lamp: 18W*1, emission of 253.7 nanometers. Consumption 350W. Standard Accessory: LED Lamp; UV Lamp*2, Base Stand, Water and Gas tap, and PRe- and HEPA-Filter. Caster :universal wheel with leveling feet. Power Supply: AC 220V, 60 Hz. Gross weight: 116 kg. Includes Compatible AVR. With 1 year warranty |   | 148,000.00                 | 148,000.00 | J. Lawilao-<br>CA Plant<br>Pathology-<br>Lab fee<br>(fiduciary) |  |
| 5   |          | unit  | VORTEX MIXER -MX-S Variable Speed Vortex Mixer. Mixing Motion: Orbital; Orbital Diameter: 4mm. Shaded pole Motor Type. 58W motor rating input. 10W motor rating output. Speed range: 0300rpm; Speed display: scale. Run Type: touch operation continuous. Dimension: 127x130x160mm (WHD). Permissible ambient temp: 5-40°C; Permissible relative humidity: 80%RH; Protection Class: IP21. Voltage: 220V, 60 Hz; 60W. Industrial Environments, Compliance Marks: CE; RCM; TUV SDO  |   | 18,000.00                  | 18,000.00  | J. Lawilao-<br>CA Plant<br>Pathology-<br>Lab fee<br>(fiduciary) |  |
|   |          |   | XXXXXXXXXXXX  |   |                            |            |   |  |
|   |          |   | TOTAL   |   |                            | 166,000.00 |   |  |
| (Total Amount in Words) One Hundred Sixty Six Thousand pesc   |          |   |   |   |                            |            |   |  |
| every day   | of delay | shall be in                                 | Fe full delivery within time specified above, a penalty of one-tenth (1/10) of one percent for imposed on the undelivered item/s.  Very Truly Yours:  FELIPE SALANG COMILA  University President  ORS/BURS No.: 2021 - 2022 - 11677   |   |                            |            |   |  |
| Funds Available:IN  |          |   | DA B. GALINATO Accountant IV  | Date of the ORS/BURS: AUG 14 2023 Amount: 106, 000 00 |                            |            |   |  |