



REQUEST FOR QUOTATION (RFQ)
(ALL ENTRIES ARE MANDATORY)

Name of Owner/ Corporation/ Cooperative/ Agency: _____

QUOTATION NO. 1378

Name of Business: _____

DATE: NOV 16 2022

Address: _____

P.R. NO.: 2022-10-1064

Email address: _____ Telephone No. _____

ABC: Php. 230,000.00

FUND SOURCE: GTA

The Benguet State University through its Rids and Awards Committee will undertake NP - SVP for the item/s listed below under the following terms and conditions:

- All entries must be written legibly and accurately.
- Delivery period is within 15 calendar days.
- Warranty period shall be for a minimum of three months, in case of expendable supplies, and a minimum of one year in case of non- expendable supplies from date of acceptance by the University.
- Price validity shall be for a period of 30 calendar days.
- Compliance with specifications: Kindly specify in the column provided below whether the offer fully complies with the specifications or a counter offer.
- Deadline of submission of quotation is on or before 5:00 PM of Nov. 21, 2022. **Offers may be submitted in sealed or open quotation in person, or through facsimile (074-661-1839) or email (procurement@bsu.edu.ph)**

7. The item/s shall be procured by: _____ a) line item; _____ b) lot; _____ c) sub-lot

8. Business Permit Number: _____, date of issue: _____, place of issue: _____
 No: _____, (If renewal of Business Permit is still on process, please indicate OR _____ for the payment of renewal).

9. * PhilGEPS Registration Number: _____

REYNANTE B. BASCO
 Chairperson, BAC (Goods & Services)

College/Dept./Office: ICT Office

Item No.	Qty	Unit	Item	Technical Specifications (Brand and Model)		Unit Cost	Total Cost
				COMPLY	COUNTER OFFER		
1	2	Set	Fiber Optic Cleaver Tool: Power Meter 5km Visual Fault Locator: Fiber cleaver: bare fiber diameter: 125um; single core, 0.25 & 0.9mm fiber coating diameter; 9-16mm (0.25mm) 10-16mm (0.9mm) fiber cutter length, cutting angle: $\le 0.5^\circ$; blade life: 40000 core wire, Size: 7.5x3x3x3mm. Optical power meter: wave length range: 800-1700nm; Connector: FC/SC/ST (optional), Standard wavelength (nm): 850/1300/1310/1490/1550/1625, Display resolution: linear display: 0.1%, logarithmic display: 0.01dBm; Red light power (one machine series) (MW): 1, 5, 10, 20, 30 (optional); battery continuous working time: >=48h; size: 180*100*48mm. Package inclusion: 1 x Optical Fiber Red Light Test Pen, 1 x CFS-2 Duplex Optical Fiber Coating Layer Stripping Pliers, 1 x Miller clamp, 1 x High Precision Optical Power Meter, 1 x fiber cut device (with some screwdriver tools), 1 x 150um bottle, 1 x black Carrying bag: 1 pcs, 1 x Fixed length rail			5,400.00	
2	1	Set	Fiber Optics Fusion Splicer Tool Set - w/ Power Meter & visual fault locator (VFL): 5 Years remote support and repair warranty, 2kg (with battery) weight, applicable fibers: SM (G.652&G.657), MM (G.651), DS(G.657), NZDS (G.655) , Splice Loss: .025dB (SM) 0.01dB (MM) 0.04dB (DS/NZDS) , 6 motors Auto focus, Fiber alignment: Core/cladding alignment Manual alignment, Typical splicing time: 5S, 1 typical heating time: 15S - Fast heating function, heating time can be set . Automatic heating (Preheating), heating programs (max:10), Real-time control and calibration of fusion ARC, Return loss: Better than 60DB, Cladding Diameter 80-150um, Coating Diameter 100-1000um, Fiber Cleave Length: Coating less than 250um : 5-19mm;Coating less m250-1000um;16mm, Shrinkable tube: 60mm, 50mm, 40mm, 25mm, 1 second booting time, Tension Test: Standard 2N, Fiber holders: 3 in 1 fiber holder, SM, MM, bare fiber, pigtail, rubber-insulated, multi fiber cable, Magnification: 300 for X or Y , 150 for XY view, 5 inch 11-1 color display screen, Software update length: Automatically update, Update by a key, Splicing Mode: Normal/high precision splicing (splicing programs max 100), Splicing method: Fully automatic, step by step splicing, Splicing record storage: Synchronize to the phone, the server to cloud storage unlimited, Built-in battery: 7800 mAh high-capacity lithium battery, charging times3.5 hours, continuous splicing and heating about 240 times, Power supply: Input AC100-240V 50 / 60HZ, output DC13.5V / 4.8A, the current power mode can be identified, real-time detection of battery power, Operating Conditions: Temperature -15 ~ +50 °C, humidity: <math>< 95\%</math> RH (no condensation), Working altitude: 0 ~ 5000m. Resist max. wind speed: $\le 15\text{m / s}$, Product protection: Waterproof IP 22, dust proof IP54, shock-resistant.			49,999.00	

3	2	Roll	Outdoor Fiber Cable: 2KM 4 Core Outdoor Optical Fiber Drop Cable, 3.8 cm min. bending angle, 0.3dB high attenuation, 0.2dB interchangeability, Waveleghth: 1310nm,1550nm, pure black color, optical fiber insertion removal times: >1000 times, reinforced w/ phosphating steel wire at 40KG tensile strength, 39.8x33.4x39.8CM, 100% brand new & High quality, with a protective corrugated steel tape for harsh outdoor applications. fiber tube surrounded in a protective gel allowing expansion and contraction of the cable without damage, unit gross weight is 40 Kg			23,000.00
4	5	Roll	Fiber Optics Cable: Mode : Single-Mode, Fiber : 2 Cores, Length : 1KM, Wavelength : 1310,1550 nm, Feature: Low fiber insertion loss<= 0.3, Light attenuation <= 0.3dB, Return Loss >= 50dB, Minimum bending radius:3.8cm, Reinforced phosphating steel wire, Low light decay,stable and fast transmission, Corrosion-resistant and flame-retardant,tensile and durable, Ceramic fiber optic ferrule, High precision ceramic ferrule,low insertion loss, Weight : 22/kg, Package includes: 1 roll * 1KM 2 cores FTTH fiber cable			29,000.00
5	50	Pcs	FTTH Fiber Panel: Fiber Optic Terminal Dual SC Junction Box, Wall Mount, 2 Cores			2,000.00
6	40	Pcs	SC BUTTERFLY CONNECTOR: SC BUTTERFLY CONNECTOR, 10 pieces with FREE STRIPPER GUIDE			42,000.00
7	60	Pcs	Fiber Optic Patch Cord: 3 meters, 9/125 Single Mode Duplex LC/UPC to SC/UPC			12,000.00
8	120	Pcs	Fiber Optic Clamp: MID SPAN FOR P-CLAMP & F-CLAMP			3,600.00
9	500	Pcs	Fiber-Optic Cable Anchoring: F Clamp/ S Clamp, for FTTH			5,000.00
10	10	Pcs	Fiber Cable Clip: 300 pieces, Double, for FTTH, with screw and tox			3,500.00
11	10	Pcs	SC-SC flange Fiber Coupler: 50 pieces, UPC			3,500.00
12	3	Pcs	RJ45 Crimp Tool Pass Through Cutter for Cat6 Cat5e 8P8C Modular			4,101.00
13	4	Roll	Ethernet Cable: indoor, CAT 6 cable, 4*2*20 AWG, 100% guaranteed pure copper UTP - marked as Oxygen Free Copper (OFC), HDPE insulation, PVC jacket, 305 Meters/1box			24,800.00
14	2	Roll	Ethernet Cable: outdoor, CAT 6 cable, 4*2*23 AWG, 100% guaranteed pure copper UTP-marked as Oxygen Free Copper (OFC), HOPE insulation, PVC+PE jacket, waterproof, black, 305 Meters in a roll, certified and tested			13,000.00
15	13	Pack	RJ 45 for Cat. 6, box of 100 pcs, CAT6a Cat6 CAT5e Pass Through RJ45 Modular Plug network Connectors UTP 30y Gold-Plated 1.2mm Hole End for Ethernet Cable			9,100.00
TOTAL						230,000.00

Counter offers:

Delivery Period: _____

Warranty: _____

Price Validity: _____

We hereby submit our quotations, accept the general conditions for the above items and be bound by our offer.

Signature over Printed Name

Date and Time of Receipt of RFQ

* Not a ground for disqualification for failure to indicate but required as a condition for award.

Revised: 9/19/2022

PPT 1004