

IB 2020-12A List of Supplies and Equipment for the Upgrading of Network / Internet Connectivity (2nd Posting)

Item No.	Unit	Item Description	Quantity	Unit Cost	Total Cost	End-user
1	unit	Router, 1U rackmount, TILE Architecture, 36 cores x 1.2GHz CPU, 8x 10/100/1000 Ethernet ports, 2x SFP+ cages, LCD, 8GB RAM, 1GB NAND storage, 41.5 mpps fastpath, Up to 28 Gbit/s throughput, SFP DDMI, RouterOS L6, 100-240VAC Dual PSU @ 73W Maximum power consumption, RJ45 Serial port, -20°C to 60°C tested ambient temperature, CLI with TELNET, SSH, Local and Serial Console, GUI via IP address and MAC address management.	2	106,000.00	212,000.00	ICT
2	unit	Layer 3 Smart Switch, 1x Gigabit Ethernet port, 16x SFP+ cages, ARM 32bit Architecture, Dual Core 800MHz CPU, 1GB RAM, 16MB FLASH storage, CLI with TELNET, SSH, Local and Serial Console, GUI via IP address and MAC address management, RouterOS L6, 100-240VAC Dual PSU @ 44W Maximum power consumption, RJ45 Serial port, -20°C to 60°C tested ambient temperature, hardware-based STP and LACP.	6	34,000.00	204,000.00	ICT
3	unit	Layer 3 Smart Switch, 24x Gigabit Ethernet PoE ports, 4x SFP+ cages, ARM 32bit Architecture, 800MHz CPU, LCD, 512MB RAM, 16MB FLASH storage, CLI with TELNET, SSH, Local and Serial Console, GUI via IP address and MAC address management, 802.3af/at PoE out, RJ45 Serial port, Metal desktop case, RouterOS L5, 100-240VAC PSU @ 20A Maximum total output and 494W Maximum power consumption (44W without attachments), RJ45 Serial port, -20°C to 60°C tested ambient temperature.	21	34,000.00	714,000.00	ICT
4	unit	Layer 3 Smart Switch, 8x Gigabit Ethernet PoE ports, 4x SFP cages, MIPSBE Architecture, 400MHz CPU, 128MB RAM, 16MB FLASH storage, CLI with TELNET, SSH, Local and Serial Console, GUI via IP address and MAC address management, 802.3af/at PoE out, RJ45 Serial port, Metal desktop case, Router OS L5, 18-57V DC Input Voltage, 160W Maximum power consumption (10W without attachments), RJ45 Serial port, -20°C to 60°C tested ambient temperature	7	16,500.00	115,500.00	ICT

5	unit	ARM 32bit Architecture, 4x 716MHz CPU, 128MB RAM, 16MB FLASH storage, CLI with TELNET, SSH, Local and Serial Console, GUI via IP address and MAC address management, RouterOS L4, 802.3af/at PoE In, Passive PoE Out up to 57V, 500mA maximum output, 24W Maximum power consumption, AC1200, 2dBi Antenna Gain for 2.4GHz, 2.5dBi Antenna Gain for 5GHz, 802.11b/g/n Dual Chain wireless, 802.11a/n/ac Dual Chain wireless, 300Mbps maximum data rate for 2.4GHz, 867Mbps maximum data rate for 5GHz, 2x Gigabit Ethernet ports, supports, IPsec hardware acceleration, -40°C to 50°C tested ambient temperature.	95	6,500.00	617,500.00	ICT
6	pc	1310nm, for up to 10 kilometer Single Mode fiber connections.	8	12,500.00	100,000.00	ICT
7	pc	10G SFP+ transceiver, Dual LC UPC connector, 850nm, 300 meter Multi-Mode fiber connections.	20	5,000.00	100,000.00	ICT
8	pc	1.25G SFP transceiver, Dual LC UPC connector, 850nm, 500 meter Multi-Mode fiber connections.	12	2,500.00	30,000.00	ICT
9	pc	6-speed RJ-45 module for up to 10 Gbps and up to 200 meter distance, supports Jumbo frames up to 10218 Bytes, supports DDM monitoring.	114	6,100.00	695,400.00	ICT
10	unit	1KVA Uninterruptable Power Supply, IEC outlet	24	12,000.00	288,000.00	ICT
11	unit	500VA Uninterruptable Power Supply, IEC outlet	8	5,500.00	44,000.00	ICT
12	pc	Motherboard Socket, X470 Chipset, 64GB maximum supported memory, supports DDR4 3600MHz, Onboard M.2 heatsink for M.2 drives, dual M.2 support, Gigabit Ethernet, USB3.1 support, USB2.0 support, SATA 6Gb/s support	2	11,000.00	22,000.00	ICT
13	pc	8-core compatible socket processor to above-defined motherboard 3.4GHz or higher base clock	2	8,500.00	17,000.00	ICT
14	pc	16 GB DDR4 memory	8	5,000.00	40,000.00	ICT
15	pc	Compatible to above defined-motherboard True-rated power supply 600W, 80Plus Silver or higher	2	4,000.00	8,000.00	ICT
16	pc	50 - 55" full HD TV	3	30,000.00	90,000.00	ICT
17	pc	500GB SSD compatible to above-defined motherboard	7	6,000.00	42,000.00	ICT
18	pc	1TB HDD SATA compatible to above-defined motherboard	2	6,000.00	12,000.00	ICT
19	pc	ATX Desktop case with 4 120mm fans or more	2	3,000.00	6,000.00	ICT

20	pc	Keyboard: plug-and-play USB connection, low-profile, quiet keys, standard layout with full-size F-keys and number pad, spill resistant, sturdy tilt legs, durable (can last up to 10 million keystrokes) and reliable keys. Mouse: plug-and-play USB connection, 1000 dpi high definition optical tracking	2	800.00	1,600.00	ICT
21	box	RJ45 – Cat5e/Cat6, 100 ohms, straight male (plug), phosphor bronze plated with 50u” gold over 100u” nickel undercoat.	1	10,000.00	10,000.00	ICT
22	box	UTP CABLE: Cat5e Unshielded Twisted Pair Cable #24AWG Bare Copper (Gray) acble, 305 meters	4	10,000.00	40,000.00	ICT
TOTAL					3,409,000.00	